

VVV

J J A

2

Toyota GT-Four Specifications

GT-FOUR

CE

CA

MODEL: ST182R-BLMVZQ

3S-GTE

ENGINE DESIGNATION: DESCRIPTION:

	Turbocharged and air-to-air intercooled front transverse- mounted, four-cylinder, in-line water-cooled four stroke, with two overhead camshafts acting directly on four valves per cylinder. Cross-flow cylinder head with pentroof combustion
	chambers, 50 degree included valve angle. Water-cooled oil cooler.
:	1998 cm3
E:	86 x 86 mm
RATIO:	8.8:1
	Twin-entry turbocharger with D-Jetronic electronic fuel injection direct into inlet ports.
	Transistorised with electronic spark advance and knock control system.
	153 kW (DIN) at 6000 rpm
	281 Nm (DIN) at 3200 rpm
	E151F
	Five-speed all synchromesh manual
	1st 3.583
	2nd 2.045
	3rd 1.333
	4th 0.972 5th 0.731
	Rev 3.153
	the state of the s

DISPLACEMENT: BORE x STROKE: COMPRESSION I INDUCTION: IGNITION:

> MAX POWER: MAX TORQUE:

TRANSMISSION

DESIGNATION: DESCRIPTION: RATIOS:

A TRANSPORT

CLUTCH:

Dry, single 236 mm diameter plate with diaphragm spring.

4WD SYSTEM DESCRIPTION:

: Viscous-coupled centre differential, non-limiting front differential, hypoid gear transfer to rear propeller shaft, torque sensing limited slip rear differental.

TRANSFER REDUCTION: 0.341

DIFFERENTIAL RATIOS: 3.933:1 (front), 2.928:1 rear

SUSPENSION

TYPE:	Fuly independent front and rear, by MacPherson struts with ball-
	joint mounted stabiliser bars.
SHOCK ABSORBE	R TYPE: Low-pressure gas-filled double acting twin-tube.
WHEELS:	15 x 6.5JJ aluminium alloy
TYRES:	215/50R15 88V Dunlop Formula V2

STEERING:

TYPE:	Engine-speed sensitive power-assisted rack and pinion
TURNS LOCK-TO-LOCK:	2.7
TURNING RADIUS:	5.5 metres (kerb-to-kerb)

BRAKES

FRONT:	277 mm ventilated disc with fully floating single-piston aluminium caliper
REAR:	288 mm solid disc with fully floating single-piston aluminium caliper
MASTER CYLINDER & SERVO:	Tandem master cylinder with tandem 7" + 9" booster

1.

Toyota's Fast February

DIMENSIONS

OVERALL LENGTH:	4430 mm
OVERALL WIDTH:	1745 mm
OVERALL HEIGHT:	1300 mm
WHEELBASE:	2525 mm
FRONT TRACK:	1475 mm
REAR TRACK:	1440 mm
KERB WEIGHT:	1390 kg (depending on options)
SEATING CAPACITY:	4
FUEL TANK CAPACITY:	68 litres



E

LI

C

CA

GT-FOUR

Toyota GT-Four Feature List

- Power-assisted rack & pinion steering
- Four-wheel disc brakes
- LED high-mount stop light
- Three-piece rear spoiler
- Dual exhaust tail pipes
- Retractable headlamps
- 8 km/h deformable colour-keyed bumpers
- Colour-keyed side protection moulding
- Electronic touch-tune AM Stereo/FM Stereo radio/ cassette with pre-programmed
 - graphic equaliser, four speakers and anti-theft system
- Power-operated rear vision mirrors
- Power-operated door locks
- Power-operated windows
- Automatic power radio aerial
- Push-button and dial a/c and heater controls
- Full sports instrumentation with tachometer, boost gauge, temperature gauge and clock
- Seven-way-adjustable sports front seats
- Top-shade laminated windscreen
- Intermittent wipers with washer-linked mist function
- Intermittent rear wiper

Toyota's Fast February

- Electric rear window demister
- Side window defogger
- Auto tilt-away steering column adjustment
- Seven-position tilt-adjustable stearing column
- Three-spoke leather covered steering wheel
- Leather-covered gear-shift and parking brake levers
- Driver's left foot rest
- Cut-pile carpet
- Fabric moulded door trims with pockets
- Locking glovebox
- Centre console box with two compartments
- Remote fuel-lid opener
- Remote boot and bonnet releases
- Instrument illumination adjustment
- Door courtesy lamps
- Ignition key lamp
- Map reading lamps
- Glove box lamp
- Ash tray lamp
- Boot lamp
- Day/night interior rear vision mirror
- Passenger assist handle and rear coat hooks
- Air conditioning (option)